

### Waschbecken


in absoluter Spitzenqualität, komplett aus NIROSTA, Mattschliff, Wandstärke 1,25 mm **ohne Fugen** dicht verschweißt, verchromter Auslauf, Elektronikeinheit mit Sensorbetätigung, Mischventil 35 – 65 °C einstellbar. Wasserzulauf 3/8", Wasserablauf 1 1/2", Netzanschluss 230 V, 50 Hz, Leistung 6 VA. Auch als Standbecken lieferbar. Auf Wunsch mit integriertem Durchlauferhitzer. (Seifenspender = Sonderausstattung)




### Basin

The ultimate in top quality, completely made of stainless steel, matt surface, 1.25 mm thick, **no joints**, sealed and welded, chromium plated outlet, electronic sensor operation, with thermostatic mixing valve, adjustable 35 – 65 °C, water intake 3/8", water outlet 1 1/2", mains voltage 230 V, 50 Hz, power 6 VA.

Also available as alone standing basin. Available with integrated continuous-flow water heater on request. (Soap dispenser = supplied separately).



X	Z	Y		Art.-Nr.
450 mm	490 mm	795 mm	~ 22 kg	5504 0100


### Waschbecken


Top-Qualität zum günstigen Preis, komplett NIROSTA, Wandstärke 1,25 mm, dreiseitig verblendet, mit Beschlägen für die Wandbefestigung, verchromter Auslauf, Elektronikeinheit mit Sensorbetätigung, Mischventil 35 – 65 °C einstellbar. Wasserzulauf 3/8", Wasserablauf 1 1/2", Netzanschluss 230 V, 50 Hz, Leistung 10 VA



### Basin

Top quality at a low price, completely made of stainless steel, 1.25 mm thick. 3-sided encasement, with fittings for wall installation, chromium plated outlet, electronic sensor operation, with thermostatic mixing valve, adjustable 35 – 65 °C, water intake 3/8", water outlet 1 1/2", Mains voltage 230 V, 50 Hz, power 10 VA



X	Z	Y		Art.-Nr.
550 mm	450 mm	270 mm	~ 9 kg	5504 0102